



Versatile Portable Projector with High Brightness

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 3,500 ANSI lumens of brightness and 15,000:1 contrast ratio for clear, crisp and bright presentations
- SVGA (800 x 600) native resolution scalable up to a maximum WUXGA (1920 x 1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports



From meeting room to presentations anywhere on the road

The DS262 is a native SVGA digital projector from Vivitek. It features DLP® and BrilliantColor™ technologies to display distinct, vibrant images in a widescreen format. The Vivitek DS262 features numerous connectivity options including two HDMI v1.4, a brightness level of 3,500 ANSI Lumens and a 15000:1 contrast ratio. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.



DS262 SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3500 ANSI Lumens
	Native Resolution	SVGA (800 x 600)
	Max. Supported Resolution	WUXGA (1920 x1200) @60Hz
	Native Aspect Ratio	4:3
	Contrast Ratio	15,000:1
	Keystone Correction	Vertical: +/-40°
Optical	Throw Ratio	1.94 - 2.32 : 1
	Zoom Ratio	1.2x
	Image Size (Diagonal)	40" - 240"
	Projection Distance	1.6 - 11.3 m
	Projection Lens	F = 2.46 - 2.66, f = 21.8 - 25.6 mm
	Offset (Based on Full Image Height)	105.7%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service)
General	Dimensions (W x D x H)	332 x 243 x 107 mm
	Weight	2.6 kg
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 203W (Eco. Mode), 240W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	5,000 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 203W
	Speakers	2W
	Noise Level	31dB / 28dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (XX5050002200), Remote Control P/N (XX5040005400), Carrying Case P/N (XX3520000800)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first
	UPC Code	813097023315