



High Brightness and Rich Functionalities for Large Venue Installation

The Vivitek D5000 is designed for large venue installations. It provides high performance brightness and image quality, in addition to being feature rich with extensive connectivity options. Using Texas Instruments DLP™ technology it is designed filter free for minimum maintenance and cleaning requirements. The D5000 is also 3D-Ready.

Features

- High Brightness with 5200 ANSI Lumen and 2500:1 contrast ratio
- Interchangeable lenses and Horizontal/Vertical lens shift capabilities
 - Full vertical/horizontal lens shift also with fixed short throw lens
- DLP® and BrilliantColor™ technologies for high contrast and superb image quality
- DLP-Link 3D-Ready for amazing 3D viewing experience
- Network-ready for integration and system administration via RJ45
- Built-in 12V trigger for external peripheral devices such as wireless modules, screens etc.

Specifications	
Brightness	5200 ANSI Lumens
Native Resolution	XGA (1024x768)
Max. Resolution	WUXGA (1920x1200) @60Hz
Contrast Ratio	2500:1 (Full On/Full Off)
Lamp Life and Type	≈1500/2000 Hours (Std./Eco Mode), 330W
Lamp Part #	5811116765-SU
Display Type	Single 0.7" DLP® Technology by Texas Instruments
Throw Ratio	1.6 to 2.0:1 (Distance/Width) with standard lens
Image Size (Diagonal)	37" to 300" (0.9 to 7.6 m)
Projection Distance	1.5 to 7m
Projection Lens	F = 2.46 - 2.56 f = 22.82 - 28.49 mm
Zoom Ratio	1.25:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Keystone Correction	Vertical: ±15°
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	50 to 85 Hz
Speakers	3Watt (x2)
Remote Control	Full Featured IR Remote with Laser Pointer
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Lens Shift Range	Vertical: -40% to +120%, Horizontal: ±10%
Uniformity	85%
Computer Compatibility	SXGA+, SXGA, WXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	Component, BNC (RGBHV), DVI-D (HDCP), HDMI v1.3, VGA-In (x2), Composite Video, S-Video, RCA Stereo Audio-In (x2), Mini-Jack Audio-In (x3), VGA-Out, Mini-Jack Audio-Out, USB (Service), RS-232c, RJ45, 12V Trigger
Weight	8.6 kg
Dimensions (W x H x D)	431 x 160.5 x 320 mm
Noise Level	37dB/33dB (Normal / Eco Mode)
Power	Supply: AC 100-240V Consumption: 335W (Economy Mode), 390W (Standard Mode), <1W (Standby Mode)
Warranty	5-Year Warranty, 1-Year or 1,000h Lamp Warranty
Standard Accessories	AC Power Cord, Component Cable, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card
Optional Accessories	Wide Fixed Lens 0.8:1, Long-Throw Lens 2.0-3.0:1
UPC with lens	814964 338310
UPC without lens	814964 338570

