



## WUXGA High Brightness Installation Projector

The D5380U offers a range of features that make it the ideal projector choice for the professional installation market. In addition to 5000 ANSI lumens of brightness, the high WUXGA image resolution delivers excellent fidelity and large screen area for simultaneous display of video conferencing, presentations, video and display of charts and graphs. With the installer in mind the D5380U features horizontal and vertical lens shift, central lens design, 3 lens options and a comprehensive range of connectivity options.

### Features

- HD WUXGA resolution
- 5000 ANSI Lumens and 2000:1 contrast ratio
- DLP® and BrilliantColor™ technologies for detailed image quality
- Centered lens for easy installation
- Three Interchangeable lens options for greater installation flexibility
- Horizontal and vertical lens shift
- Connectivity options including: HDMI v1.4, DisplayPort, VGA-Out, RJ45 and RS-232
- DisplayPort connector for digital audio and video signals
- Built-in 12V trigger for external wireless module connection
- Audio ready with 2x3W stereo speakers

| Specifications                             |  |
|--|--|
| Brightness                                 | 5000 ANSI Lumens   |
| Native Resolution                          | WUXGA (1920 x 1200)  |
| Maximum Resolution                         | WUXGA (1920 x 1200) @60Hz  |
| Contrast Ratio                             | 2000:1   |
| Lamp Life and Type                         | 1,500/3,500 hours (Normal/Eco Mode) 370W/280W  |
| Display Type                               | Single 0.67" DLP Technology by Texas Instruments   |
| Throw Ratio                                | 1.54 - 1.93:1 (std lens)   |
| Image Size (Diagonal)                      | 36.1"-210" (std lens)  |
| Projection Distance                        | 1.5 to 7m (std lens)   |
| Projection Lens                            | F = 2.46 - 2.56 f = 22.82 - 28.49mm (std lens)   |
| Zoom Ratio                                 | 1.25x (std lens)   |
| Aspect Ratio                               | 16:10 Native, 4:3 and 16:9 Compatible  |
| Offset                                     | Manual Lens Shift  |
| Keystone Correction                        | Vertical ±15°  |
| Speakers                                   | 3 Watt x 2 (stereo)  |
| Lens Shift Range (full image height/width) | Vertical: -15% to +55%<br>Horizontal: +/-5%  |
| Video Compatibility                        | SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)  |
| I/O Connection Ports                       | VGA-In (2x), HDMI v.1.4b, DisplayPort, DVI-D, Component (5-BNC), Component (3xRCA), S-Video, Composite, Audio-In (RCA) (2X), Audio-In (Mini-Jack)(2X), Audio-Out (Mini-Jack), RJ-45, RS-232, 12V-trigger, 3D-Sync-Out, USB Type-A (power only), Remote-Jack (for wired R/C), VGA-out(1x) |
| Projection Method                          | Table Top, Ceiling Mount (Front or Rear)   |
| Security Solutions                         | Kensington® Security Slot, Security Bar, Keypad Lock   |
| Dimensions (W x D x H)                     | 431 x 320 x 160.5 mm   |
| Weight                                     | 8.6kg  |
| Noise Level                                | 42dB/37dB (Normal/Eco Mode)  |
| Power                                      | 450W (Normal Mode), 340W (Eco Mode), Standby <0.5W   |
| Warranty                                   | 5-Year Warranty, 1-Year or 1000h Lamp Warranty   |
| Standard Accessories                       | AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit  |
| Optional Accessories                       | Replacement Lamp, Remote, 3 Interchangeable Lens Options   |
| UPC without lens                           | 814964 338761  |

### Photos



| Optional Lens Details |               |               |               |
|-----------------------|---------------|---------------|---------------|
| Lens                  | Short Throw   | Standard      | Long Throw    |
| Part Number           | 5811116225-SU | 5811116223-SU | 5811116224-SU |
| Throw Ratio           | 0.77:1        | 1.54~1.93:1   | 1.93~2.89:1   |
| Zoom Ratio            | N/A           | 1.25          | 1.5           |
| F                     | 11,5          | 22.8 ~ 28.5   | 28.5~42.75    |
| F#                    | 2.5           | 2.46~2.56     | 2.5~3.1       |
| Screen Size           | 30.2-181"     | 36.1~210"     | 32.1~481"     |
| Projection Distance   | 0.5- 3.0m     | 1.5-7m        | 2.0-20m       |