



WXGA projector with built-in 2D to 3D content conversion technology

The Vivitek D803W-3D proposes a native WXGA resolution for wide image display. In addition to combining 3,600 ANSI lumens of brightness and a high contrast ratio of 15,000:1, the projector integrates the DLP® and BrilliantColor™ technologies from Texas Instruments to ensure sharp and dazzling images projection. D803W-3D, is ideally suited for multimedia and video applications, the D803W-3D has direct 3D capabilities over HDMI v1.4 and can also convert 2D digital signals to 3D without the use of an external converter box.

Features

- Bright 3600 ANSI lumens and a crisp 15,000:1 contrast ratio for a perfect image
- WXGA native resolution for wide image display
- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Connectivity options including: HDMI v1.4 (x2), VGA-In, S-Video, Component (YPbPr), Composite Video, Audio-In and RS-232C
- Integrated 2D to 3D content conversion technology
- Sealed optical engine to keep dust out
- Top-loading, sliding cover for quick and easy lamp replacement
- Built-in 10W audio speaker
- Kensington® security slot, security bar, keypad lock for added security
- Great portability at 2.7kg

Product Pictures



Specifications	
Brightness	3600 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	UXGA (1600 x 1200)
Contrast Ratio	15000 :1
Lamp Life and Type	3000/4000 Hours (Bst/Std. Mode) 240W/190W
Display Type	0.65" (WXGA) DLP® Technology by Texas Instruments
Image Size (Diagonal)	27" - 302" (68.6 - 767.1cm)
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F=2.50~2.72, f = 17.81~21.35mm
Zoom Ratio	1.1x
Aspect Ratio	16:10 Native, 4:3, 16:9 Compatible
Throw Ratio	1.54 - 1.71:1
Offset	123% +/-10%
Keystone Correction	Vertical +/- 40°
Horizontal Frequency	15, 31-102KHz
Vertical Scan Rate	48 - 120Hz
Speakers	10W (Mono)
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4a (3D features) (x2), VGA-In, S-Video, Component (YPbPr), Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS-232C, mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x W)	285 x 261 x 122 mm (11.2" x 10.3" x 4.8")
Weight	2.7Kg
Noise Level	32/34 (Std. /Boost Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	230W (Std. Mode), 260W (Boost. Mode), <0.5W (Standby)
Warranty	3-Year Warranty, 1-Year or 1,000h on Lamp
Educational Warranty	5-Year Warranty, 3-Year (or max. Lamp Lifetime)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	814964336910

