



The H1185HD is Vivitek's new Full HD 3D projector. With a great brightness of 2500 ANSI lumen and a contrast ratio of 10,000:1 giving an excellent level of black, the H1185HD is the perfect projector to entertain in a variety of moderate lighting environments. Also thanks to its new generation lamp the H1185HD will allow an extended lamp life up to 5,000 hours. The new embedded 1080p chipset will help deliver amazing viewing experience in either 2D or in 3D.

## Features

- Full high definition 1080p (1920x1080) resolution for the best quality, sharpness and clarity of video
- Super bright at 2500 ANSI lumens for vibrant and dazzling images
- 10,000:1 contrast ratio for crisp pictures
- DLP® DarkChip3™ and BrilliantColor™ technologies from Texas Instruments
- ISF mode for day and night calibration
- SRS WOW® significantly improves the playback quality of audio, delivering a dynamic 3D entertainment experience with deep, rich bass
- High-efficiency lamp that last up to 5000 hours (in economy mode)
- Host of connectivity options including HDMI v1.4, VGA-in, S-video, component and composite
- 3D-ready via DLP® Link™ and BluRay 3D movie playback
- Top sided lamp cover for convenient lamp replacement
- Built-in 10W audio speaker

Specifications	
Display Type	DLP® 0.65 Dark Chip 3™ BrilliantColor™ Technology
Brightness	2500 ANSI Lumens
Native Resolution	1080p (1920 x 1080)
Maximum Resolution	WUXGA 1920x1200@60Hz
Contrast Ratio	10,000:1
Lamp Life and Type	3,500/5,000 Hours (Normal/Eco Mode), 240W/190W
Throw Ratio	1.39 – 2.09:1
Image Size (Diagonal)	26.2"-329"
Projection Distance	1.2 - 10m
Projection Lens	F=2.418~2.97 (TBD) , f = 20.7~31.05mm
Zoom Ratio	1.5x
Aspect Ratio	16:9 Native
Offset (full image height)	115%
Keystone Correction	Vertical ± 40%
Speakers	SRS WOW®, 10W (Mono) Speaker
3D Ready	Yes, Direct 3D
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4 (x2), Component (YPbPr RCAx3), VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), 12V Trigger, RS-232, 3D Sync-Out, USB Power (5V,1.5A), Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x H)	285 x 261 x 121.8 mm
Weight	3.15 Kg
Noise Level	35dB/32dB (Normal /Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal/Eco Mode) <0.5W (Standby Mode)
Warranty	3 Years, 1 Year (or 1,000h) on the Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote Control
UPC	814964 33473 2

## Product Pictures

