



Versatile Portable Projector with High Brightness

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- Short throw lens delivers 100" image at only 1.3m away
- 3,200 ANSI lumens of brightness and 15,000:1 contrast ratio for clear, crisp and bright presentations
- XGA (1024 x 728) native resolution and support up to maximum WUXGA (1920x1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports



Short throw lens delivers 100" image at only 1.3m away

The DX281-ST projector delivers a 100" diagonal image at only 1.3 meters projection distance. With a brightness of 3,200 ANSI Lumens and contrast ratio of 15,000:1 it delivers a perfect image display. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.



DX281-ST SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3200 ANSI Lumens
	Native Resolution	XGA (1024 x 768)
	Max. Supported Resolution	WUXGA (1920 x1200) @60Hz
	Native Aspect Ratio	4:3
	Contrast Ratio	15,000:1
	Keystone Correction	Vertical: +/-40°
Optical	Throw Ratio	0.63 : 1
	Zoom Ratio	1x
	Image Size (Diagonal)	56" - 120"
	Projection Distance	54 - 154 cm
	Projection Lens	F = 2.7, f = 7.2 mm
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service)
General	Dimensions (W x D x H)	332 x 243.6 x 107 mm
	Weight	2.6 kg
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 203W (Eco. Mode), 240W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	5,000 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 203W
	Speakers	2W
	Noise Level	31dB / 28dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (XX5050002200), Remote Control P/N (XX5040005400), Carrying Case P/N (XX3520000800)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first
	UPC Code	813097023353