



PROJECTOR **D538W-3D**

Taking 3D Projection to Another Dimension

From converting traditional 2D content into 3D to projecting 3D content from pretty much any video source without an external box, the Vivitek D538W-3D digital projector takes 3D to another level.

Features

- Bright 3200 ANSI Lumens and a crisp 3000:1 contrast ratio for a perfect image
 - Integrated 2D to 3D content conversion technology
 Can automatically converts any 2D content into 3D ready material through HDMI port by pressure of a single button for enhanced viewing pleasure
- WXGA native resolution for wide image display (HD720p compatible)
- DLP[®] and BrilliantColor[™] technologies for sharp and detailed image quality
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- High brightness and contrast ratio
- 3D ready for gaming and movies
- Connectivity options including: HDMI v.1.3, and RS-232C
- Keypad lock prevents accidental system adjustments
- Great portability at 1.9kg

Product photos



Specifications	
Brightness	3200 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200) @60Hz
Contrast Ratio	3000 :1
Lamp Life and Type	3000/4000 Hours (Std. /Eco. Mode), 240W
Display Type	Single 0.95" DLP [®] Technology by Texas Instruments
Throw Ratio	1.52 - 1.76:1
Image Size (Diagonal)	31"- 300"
Projection Distance	1.2 - 10m
Projection Lens	F = 2.52 - 2.72, f = 21.35 - 24.49mm
Zoom Ratio	1.15x
Aspect Ratio	16:10 Native, 4:3, 16:9 Compatible
Offset	120%
Keystone Correction	Vertical ± 15°
Horizontal Frequency	15, 30-90KHz
Vertical Scan Rate	43 - 85Hz
Speakers	2 Watt
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p,
	1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H,
	I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v.1.3, VGA-In, S-Video, Composite Video,
	Audio-In RCA (L/R), Audio-In (Mini-Jack), RS-232C
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington [®] Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x W)	261 x 190 x 78mm
Weight	1.9kg
Noise Level	35dB/29dB (Normal / Eco Mode)
Power Consumption	Supply: AC 100-240V, 50/60Hz
	Consumption: 230W (Eco. Mode), 300W (Std.
	Mode), <1W (Standby)
Warranty	3-Year Warranty, 1-Year or 1,000h on Lamp
Education Warranty	5-Year Warranty, 3-Year (or max. Lamp Lifetime
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote
	Control, Batteries for Remote, Lens Cap,
	Documentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case







© Copyright 2013 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Address: Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands, Tel: +31 20 655 0960, Fax: +31 20 655 0999, E-Mail: info@vivitek.eu